

FLEXITEX

CODE:

DTF

DESCRIPTION:

A strong flexible acrylic texture coating.

PRODUCT BENEFITS:

Formulated as a decorative textured finish.
Its special properties ensures the coverage of hairline cracks with the flexibility to cope with the expansion and contraction of plaster surfaces.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces, e.g. new mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer/Acid Etch Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer

PRECAUTIONS:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Stir thoroughly with flat paddle before use.
Ready for use by brush or roller. Apply 2 coats. Clean up with water.

TECHNICAL DATA:

SG:	1.55 +/- 0.05
Drying Time: (T)	1 hour
@ 25°C (H):	4 hours
Recoat:	4 hours
Finish:	Textured
Viscosity:	115 - 120 KU
Spread Rate:	Approx. 4 - 5m ² /Lt.
Colour Range:	Range of ready mixed colours
Pack Size:	5L & 20L

Health and Safety:

Refer to Material Safety Data Sheet