

# SUPER ACRYLIC

**CODE:****DSA****Description:**

A durable matt acrylic emulsion.

**Product Benefits:**

Low dirt retention, washable and flexible.

**SURFACE PREPARATION:****New Work:**

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer/Acid Etch Primer.

**Previously Painted Surfaces:**

1. Surfaces must be sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

**General:**

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.

**APPLICATION:**

Ready to use with brush, roller or airless spray application. Apply 2 coats. Clean with water.

**TECHNICAL DATA:****SG:**

1.54 +/- 0.05

**Viscosity:**

100 - 105 KU

**Drying Time: (T)**

1 hour

**@ 25°C: (H)**

4 hours

**Overcoating:**

2 hours

**Solid Mass:**

+/- 60%

**Finish @85°:**

4 - 7% Matt

**Spread Rate:**7 - 8m<sup>2</sup>/Lt dependent on substrate**Scrubs:**

10,000

**Colour Range:**

White

**Bases:**

Pastel, Deep, Transparent

Note: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.

**Health and Safety:**

Refer to Material Safety Data Sheet