

PINK WOOD PRIMER

CODE:

TPW

DESCRIPTION:

Essentially a primer for new wooden surfaces. Provides excellent adhesion for subsequent overcoating with Trade Undercoat and Dekade Alkyd Topcoats i.e. Trade Gloss Enamel.

PRODUCT BENEFITS:

A general purpose oil based wood primer for interior/exterior use. Good penetration and sealing properties ensures protection for all new unpainted timber. Economical to use and easy to apply.

SURFACE PREPARATION:

All surfaces must be clean and dry (borer or fire retardant timber can cause slow drying of the primer). Special attention must be given to painting the end grain of the timber to avoid moisture penetration. Previously painted surfaces which are in a sound condition do not require priming. Flaking or loose paint should be stripped back to bare wood and treated as new wood.

GENERAL:

Do not use as a metal or plaster primer. Do not paint on wet timber. Not recommended for resinous timber.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush. Better penetration achieved when applied with a brush. Thin with Mineral Turps. Clean up with Mineral Turps or Trade Degreaser.

TECHNICAL DATA:

Type:	Oleoresinous
Drying Time: (T)	4 Hours
@ 25°C (H):	24 Hours
Recoat:	16 Hours
Viscosity:	65 - 70 KU
SG:	1.46 - 1.48
Solids by Volume:	48 - 50%
Spread rate:	Approx. 8m ² /L
Solids by Mass:	66 - 68%
Flashpoint:	37°C
Colour Range:	Pink
Pack Sizes:	5lt & 20lt
Finish:	Matt

Health and Safety:

Refer to Material Safety Data Sheet