



CRAFTSMAN NUKOTE



PRODUCT USES

Primarily used on new plastered walls where a quick drying matt finish is required.

May also be used as a low cost finish for interior ceiling boards.



FEATURES AND BENEFITS

Low cost PVA, specifically formulated for contractors requirements.

Quick drying time.

Good obliteration and over-coating properties.



PRODUCT INFORMATION

Appearance	Matt
Colour	White and Colours: Soft Peach and Cream
Density at 23°C	Approx. : 1.40 kg/L
Solids Content	By weight : Approx. 48% By volume : Approx. 27%
Packaged Viscosity	Viscosity at 23°C : Approx 115 KU
Spreading Rate	Approx 8m ² per litre depending on surface porosity, profile and application method
Recommended DFT per coat	Min. 20µm. Max. 35µm.



APPLICATION INFORMATION

Application conditions	Surface Temperature between 10 - 35°C Relative Humidity between 10 - 85 %
Application methods	Brush, lamb's wool roller or spray
Thinner	Thinning not recommended Ready for use after thorough stirring
Drying Time	Touch dry 30 minutes (Drying times will be extended during cold, wet or humid conditions)
Recoating Time	3 hours
Cleaning of equipment	Clean immediately with water
Substrates	Suitable for cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards.

Low cost,
quick drying,
general purpose
matt PVA





20L



10L



5L



APPLICATION INFORMATION

Precautions

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Do not apply directly to bare metal surfaces.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

For areas subject to continual handling/soiling, e.g. cupboards and doors, use **Dulux Pearlgló Enamel**.

Coats Required

Apply two to three finishing coats to new surfaces to achieve a closed film and solid colour.



SURFACE PREPARATION

NEW SURFACES

Cement Plaster (non friable), Gypsum Plaster, Composition Boarding, Fibre Cement

It is recommended that fresh plaster should be allowed one week drying for every 5mm thickness; and longer in cold or damp weather.

Spot-prime metal strips and nail heads with appropriate metal primer.

Prime with one full coat **Dulux Primer for New Plaster**.

Concrete

Remove any uncured cement, grease, and mould-release agents by high-pressure water blast, or wash with a strong solution of sugar soap. Rinse off thoroughly with clean water.

Prime with one full coat **Dulux Primer for New Plaster**.

PREVIOUSLY PAINTED SURFACES

Sound, not powdery

Wash down with water, and then follow with two finishing coats.

Sand enamel surfaces to a matt finish to aid adhesion and apply two finishing coats.

Old Paint in Poor Condition

Strip loose and flaking paint completely and spot prime bare areas with **Dulux Primer for New Plaster**.

Friable and porous surfaces must be removed and repaired.

Filling

Fill and repair imperfections with the appropriate **Fixit Filler** and prime with **Dulux Primer for New Plaster** once the crack filler has dried properly. Failure to do this will result in uneven sheen levels between the repaired and normal areas.



HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



ADDITIONAL INFORMATION

Storage Conditions

Store under cool dry conditions.

Disclaimers

For best colour and sheen consistency, it is advisable to use containers of the same batch number, or to mix different batches together in a large container, or to finish in a corner before starting a new container.