MIX & MEND CRACK FILLER

CODE: **PMM**

DESCRIPTION:

Prepfix Mix & Mend is a white cement-based filler for filling cracks and imperfections on plaster, masonry surfaces, brick, fibre cement and wooden products. Prepfix Mix & Mend is suitable for filling up to 5mm thick.

BENEFITS & FEATURES:

- Hard, stable, weather resistant filler.
- Does not shrink or crack when applied up to 5mm thick.
- Excellent adhesion.
- Ease of use - easy to apply and achieve good results.
- White finish - easy to cover with paint.

PRODUCT USES:

- Filling cracks and imperfections on plaster and gypsum board walls and ceilings.
- It can be used for skimming and repairing uneven walls (When used as Prepfix Styrobond).
- Suitable for interior and exterior use.

SURFACE PREPARATION:

- Surfaces should be clean and dry.
- Friable surfaces should be prepared and primed with surface conditioner.
- All loose and inadequately adhering paint should be removed.
- Nail heads should be primed with rust & metal primer before filler is applied.
- V out small cracks to allow proper filling.

MIXING:

- Mix 2 parts Mix & Mend with 1 part water.
- Mix thoroughly to ensure stiff and lump free paste.
- When used as a skimming plaster: add 2 parts Prepfix Mix & Mend to 1 Part Solution (60% Water / 40% Prepfix Styrobond) and mix well.

APPLICATION:

- Apply Mix & Mend mixed paste and work with putty knife or scraper.
- Fill the crack slightly proud to allow for sanding.
- Work the surface level with a wet scraper before completely dry.
- Deep cavities may need extended drying times - allow overnight drying.
- Drying times will be extended during cold periods.

OVERCOATING:

- All filled areas should be primed with Deco / Dekade Plaster Primer.
- Allow to dry and continue with topcoats.

MIX & MEND CRACK FILLER (continued)

EXCLUSIONS:

- Not for use on softwoods that will adversely be affected by the moisture content of the mixed filler.
- Not suitable for structural repairs.
- Mix & Mend is not recommended for flexible surfaces.
- Flexible surfaces should be filled with Prepfix Fibre-reinforced Prepfix Flex & Fill.

CLEANING OF EQUIPMENT:

- Remove as much product from tools with paper towel and then wash with warm water.
- Do not wash into drains.
- Any unused product should be allowed to dry and then discarded.
- Prepfix Water Based Degreaser will aid easy cleaning.

PRECAUTIONS:

- Do not apply when temperatures are below 10°C.
- Always prime friable surfaces prior to filling.
- Prepfix Masonry Crack Filler is preferred for exterior masonry repairs.
- Ensure the packets are properly sealed after use to prolong shelf life.
- Shelf life is 12 months if sealed and stored in a cool dry environment.
- Do not use to fill softwoods, moisture will cause these to swell.

HEALTH & SAFETY:

- **Keep out of reach of children.**
- Product contains no added lead.
- Contact with skin must be avoided.
- Avoid contact with eyes.
- If accidentally swallowed, seek medical advice - Do NOT induce vomiting.
- Use suitable respiratory protection when sanding to avoid inhalation of dust.
- Do not wash equipment or leftover products into drains, allow to dry and then dispose in accordance with local regulations.
- For detailed information refer to Safety Data Sheet (SDS).

PACKAGING:

- Supplied in resealable 500mg and 2kg packs and 10kg Bulk Bags.
- 30kg available on request.

TECHNICAL DATA:

Appearance:	Powder
Colour:	White
Set time:	+/- 4 hours @ 20ºC
Pot Life:	+/- 60 minutes
Flash Point:	N/A